LIFE SCIENCES IMPLANT LINE

MED-6385 LOW CONSISTENCY SILICONE ELASTOMER

## **DESCRIPTION**

## **APPLICATION**

- Pourable, two-part silicone elastomer
- Cures at room temperature upon exposure to atmospheric moisture
- 100:0.5 Mix Ratio (Base: Curing Agent)

 For use in potting, encapsulating, coating, and injection or transfer molding applications

NuSil Technology's MED-6385 may be considered for use in human implantation for a period of greater than 29 days.

## **PROPERTIES**

TYPICAL PROPERTIES	AVERAGE RESULT	STANDARD	NT-TM
Uncured:			
Appearance	Gray to Tan	ASTM D2090	002
Viscosity	45,000 cP (45,000 mPas)	ASTM D1084, D2196	001
Work Time	7.5 minutes	-	800
Cured: 24 hours at ambient temperature and humidity			
Specific Gravity	1.13	ASTM D792	003
Durometer, Type A	45	ASTM D2240	006
Tensile Strength	500 psi (3.4 MPa)	ASTM D412	007
Elongation	175%	ASTM D412	007
Tissue Culture (Cytotoxicity Testing)	Pass	USP <87>	061
		ISO 10993-5	
Elemental Analysis of Trace Metals	Pass	ASTM E305	131

The above properties are tested on a lot-to-lot basis. Do not use as a basis for preparing specifications. Please <u>contact</u> NuSil Technology for assistance and recommendations in establishing particular specifications.



## INSTRUCTIONS FOR USE

#### Mixing

Add 0.5% by weight catalyst to the base material and mix thoroughly for two mintues. If an air-free mixture is desired, then vacuum de-air the mixture to minimize trapped air bubbles.

#### Vacuum Deaeration

Remove air entrapped during mixing by common vacuum deaeration procedure, observing all applicable safety precautions. Slowly apply full vacuum to a suitable container of at least four times the volume of material being de-aired. Hold vacuum until bulk deaeration is complete.

#### **Cure Inhibition**

Curing may be inhibited by traces of amines, sulfur, nitrogen oxide, organotin compounds, and carbon monoxide. Because organic rubbers often contain these substances, they should not come in contact with the uncured elastomer. Catalyst residues from silicone RTV elastomers and peroxide-cured silicone elastomers may also inhibit the cure.

#### Packaging

- 1 Pint Kit (458 g)
- 1 Gallon Kit (3.66 kg)
- 5 Gallon Kit (18.3 kg)

#### Warranty

6 Months

Note: Some bonding applications may require the use of a primer. NuSil Technology's MED1-161 is suggested. For more information on primer selection, visit <a href="https://www.nusil.com">www.nusil.com</a> and review <a href="https://www.nusil.com">Choosing a Silicone Primer/Adhesive System</a>.

#### FDA MASTER FILE

A Master File for MED-6385 has been filed with the U.S. Food and Drug Administration. Customers interested in authorization to reference the Master File must contact NuSil Technology.

#### REACH COMPLIANCE

MED-6385 is compliant with the Registration, Evaluation, and Authorization of Chemicals (REACh) regulation (European Union 1907/2006). MED-6385 does not contain any of the chemicals or substances identified as Substances of Very High Concern (SVHC) by the European Chemicals Agency (ECHA), which oversees REACh compliance.

Please contact NuSil Technology's Regulatory Compliance department with any questions or for further assistance.

## **SPECIFICATIONS**

Do not use the properties shown in this technical profile as a basis for preparing specifications. Please <u>contact</u> NuSil Technology for assistance and recommendations in establishing particular specifications.



#### WARRANTY INFORMATION

The warranty period provided by NuSil Technology LLC (hereinafter "NuSil Technology") is 6 months from the date of shipment when stored below 40°C in original unopened containers. Unless NuSil Technology provides a specific written warranty of fitness for a particular use, NuSil Technology's sole warranty is that the product will meet NuSil Technology's then current specification. NuSil Technology specifically disclaims all other expressed or implied warranties, including, but not limited to, warranties of merchantability and fitness for use. The exclusive remedy and NuSil Technology's sole liability for breach of warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. NuSil Technology expressly disclaims any liability for incidental or consequential damages.

#### WARNINGS ABOUT PRODUCT SAFETY

NuSil Technology believes, to the best of its knowledge, that the information and data contained herein are accurate and reliable. The user is responsible to determine the material's suitability and safety of use. NuSil Technology cannot know each application's specific requirements and hereby notifies the user that it has not tested or determined this material's suitability or safety for use in any application. The user is responsible to adequately test and determine the safety and suitability for their application and NuSil Technology makes no warranty concerning fitness for any use or purpose. NuSil Technology has completed no testing to establish safety of use in any medical application.

NuSil Technology has tested this material only to determine if the product meets the applicable specifications. (Please <u>contact</u> NuSil Technology for assistance and recommendations when establishing specifications.) When considering the use of NuSil Technology products in a particular application, review the latest Material Safety Data Sheet and <u>contact</u> NuSil Technology with any questions about product safety information.

Do not use any chemical in a food, drug, cosmetic, or medical application or process until having determined the safety and legality of the use. The user is responsible to meet the requirements of the U.S. Food and Drug Administration (FDA) and any other regulatory agencies. Before handling any other materials mentioned in the text, the user is advised to obtain available product safety information and take the necessary steps to ensure safety of use.

## PATENT / INTELLECTUAL PROPERTY WARNING

NuSil Technology disclaims any expressed or implied warranty against the infringement of any domestic or international patent/intellectual property right. NuSil Technology does not warrant the use or sale of the products described herein will not infringe the claims of any domestic or international patent/intellectual property right covering the product itself, its use in combination with other products, or its use in the operation of any process.



# Polymer Systems Technology Limited



## Silicone Sales & Services UK - Ireland - Benelux

#### © 2014 - Polymer Systems Technology Limited™ Unit 2. Network 4. Cressex Business Park, Lincoln Road, High Wycombe, Bucks. HP12 3RF

Phone +44 (0) 1494 446610 Web: http://www.silicone-polymers.co.uk Email: sales@silicone-polymers.co.uk

