

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 28/08/2020 Date of issue: 29/05/2014

Version: 3.0

# SECTION 1: Identification of the Substance/mixture and of the Company/Undertaking

#### 1.1. Product Identifier

Product form Mixture
Product Name CV-1146-2

## 1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

#### 1.2.1. Relevant Identified Uses

Use of the Substance/Mixture For professional use only.

## 1.2.2. Uses Advised Against

No additional information available

## 1.3. Details of the Supplier of the Safety Data Sheet

NuSil Technology Europe 1198 Avenue Maurice Donat Le Natura Bt. 2

06250 Mougins

France

+33 4 92 96 93 31

ehs@nusil.com

www.nusil.com

## 1.4. Emergency Telephone Number

Emergency Number : 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC

(International and Maritime)

+(44)-870-8200418 +(353)-19014670

## **SECTION 2: Hazards Identification**

#### 2.1. Classification of the Substance or Mixture

Classification According to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Skin Irrit. 2 H315
Eye Irrit. 2 H319
Skin Sens. 1 H317
STOT SE 3 H336
Asp. Tox. 1 H304
Aquatic Chronic 3 H412

Full text of hazard classes and H-statements: see section 16

#### 2.2. Label Elements

Signal Word (CLP)

Labelling According to Regulation (EC) No. 1272/2008 [CLP]

Hazard Pictograms (CLP)

GHS02 GHS07 GHS

GHS02 GHS

Danger

Hazardous Ingredients Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics; 2-

28/08/2020 EN (English) 1/14

## Hazard Statements (CLP)

Butanone, O,O',O''-(methylsilylidyne)trioxime; 1-Propanamine, 3-(triethoxysilyl)-; N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine

H225 - Highly flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

## Precautionary Statements (CLP)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground and bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating, and lighting equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P261 - Avoid breathing vapors, mist, or spray

P264 - Wash hands, forearms and face thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear eye protection, face protection, face shield, protective clothing, protective gloves

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P302+P352 - IF ON SKIN: Wash with plenty of water

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTRE or doctor if you feel unwell.

P321 - Specific treatment (see Section 4 on this SDS)

P331 - Do NOT induce vomiting.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), foam, sand to extinguish

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special

28/08/2020 EN (English) 2/14

waste collection point, in accordance with local, regional, national and/or international regulation.

#### 2.3. Other Hazards

Other Hazards Not Contributing to the Classification

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

## **SECTION 3: Composition/Information on Ingredients**

## 3.1. Substances

Not applicable

## 3.2. Mixtures

Name	Product Identifier	%	Classification According to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	(CAS-No.) Not available (REACH Registration No.) 01-2119473851-33 (EC-No.) 920-750-0	10 - 30	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
2-Butanone, O,O',O''- (methylsilylidyne)trioxime	(CAS-No.) 22984-54-9 (EC-No.) 245-366-4	< 10	Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT RE 2, H373
Silica, amorphous, fumed, crystalline-free	(CAS-No.) 112945-52-5 (EC-No.) 601-216-3	< 10	Not classified
1-Propanamine, 3- (triethoxysilyI)-	(CAS-No.) 919-30-2 (EC-No.) 213-048-4 (EC Index-No.) 612-108-00-0	< 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Irrit. 2, H319 Skin Sens. 1, H317
N-[3-(TrimethoxysilyI)propyI]- 1,2-ethanediamine	(CAS-No.) 1760-24-3 (EC-No.) 217-164-6	< 1	Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Dam. 1, H318 Skin Sens. 1, H317
Dibutyltin dilaurate	(CAS-No.) 77-58-7 (EC-No.) 201-039-8 (EC Index-No.) 050-030-00-3	< 0,1	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

## **SECTION 4: First Aid Measures**

## 4.1. Description of First-aid Measures

First-Aid Measures General

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

28/08/2020 EN (English) 3/14

First-Aid Measures After Inhalation	When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.
First-Aid Measures After Skin	Immediately remove contaminated clothing. Immediately
Contact	drench affected area with water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists.
First-Aid Measures After Eye	Immediately rinse with water for at least 15 minutes. Remove
Contact	contact lenses, if present and easy to do. Continue rinsing.
	Obtain medical attention.
First-Aid Measures After	Do NOT induce vomiting. Rinse mouth. Immediately call a

Ingestion POISON CENTER or doctor/physician.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Effects Causes serious eye irritation. Causes skin irritation. Skin

sensitisation. May cause drowsiness and dizziness. May be fatal

if swallowed and enters airways.

Symptoms/Effects After High concentrations may cause central nervous system

Inhalation depression such as dizziness, vomiting, numbness, drowsiness,

headache, and similar narcotic symptoms.

Symptoms/Effects After Skin Redness, pain, swelling, itching, burning, dryness, and

Contact dermatitis. May cause an allergic skin reaction.

Symptoms/Effects After Eye Contact causes severe irritation with redness and swelling of the

Contact conjunctiva.

Symptoms/Effects After Aspiration into the lungs can occur during ingestion or vomiting

Ingestion and may cause lung injury.

Chronic Symptoms Repeated exposure may cause skin dryness or cracking.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## **SECTION 5: Firefighting Measures**

## 5.1. Extinguishing Media

Suitable Extinguishing Media Dry chemical powder, alcohol-resistant foam, carbon dioxide

(CO<sub>2</sub>). Water may be ineffective but water should be used to

keep fire-exposed container cool.

Unsuitable Extinguishing Media Do not use a heavy water stream. A heavy water stream may

spread burning liquid.

## 5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard Highly flammable liquid and vapour.

Explosion Hazard May form flammable or explosive vapour-air mixture.

Reactivity Reacts violently with strong oxidisers. Increased risk of fire or

explosion.

Hazardous Decomposition Products in Case of Fire

Carbon oxides (CO, CO<sub>2</sub>). Silicon oxides. Hydrocarbons.

5.3. Advice for Firefighters

Precautionary Measures Fire Exercise caution when fighting any chemical fire.

of major fire and large quantities: Evacuate area. Fight fire

remotely due to the risk of explosion.

Protection During Firefighting Do not enter fire area without proper protective equipment,

including respiratory protection.

28/08/2020 EN (English) 4/14

Other Information Do not allow run-off from fire fighting to enter drains or water

courses.

## **SECTION 6: Accidental Release Measures**

## 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures Avoid breathing (vapor, mist, spray). Avoid all contact with skin,

eyes, or clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use

special care to avoid static electric charges.

6.1.1. For Non-Emergency Personnel

Protective Equipment Use appropriate personal protective equipment (PPE). Emergency Procedures Evacuate unnecessary personnel. Stop leak if safe to do so.

**6.1.2.** For Emergency Responders

Protective Equipment Equip cleanup crew with proper protection.

Emergency Procedures Upon arrival at the scene, a first responder is expected to

recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

Eliminate ignition sources.

#### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

## 6.3. Methods and Materials for Containment and Cleaning Up

For Containment Contain any spills with dikes or absorbents to prevent migration

and entry into sewers or streams. As an immediate

precautionary measure, isolate spill or leak area in all directions.

Methods For Cleaning Up

Clean up spills immediately and dispose of waste safely. Absorb

and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Transfer spilled material to a suitable container for disposal. Use only non-sparking tools. Contact competent authorities after a

.llias

## 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## **SECTION 7: Handling And Storage**

#### 7.1. Precautions for Safe Handling

Additional Hazards When Handle empty containers with care because residual vapours

Processed are flammable.

Precautions for Safe Handling Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, mist, spray. Take precautionary measures against static discharge. Use only non-sparking tools. Wash hands and other exposed areas with mild soap and water before eating,

cxposed areas with thind soup and water before e

drinking or smoking and when leaving work.

Hygiene Measures Handle in accordance with good industrial hygiene and safety

procedures.

28/08/2020 EN (English) 5/14

## 7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures Comply with applicable regulations. Take action to prevent

static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and

lighting equipment.

Storage Conditions Store in a dry, cool place. Keep/Store away from direct sunlight,

extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in

fireproof place.

Incompatible Materials

Strong acids, strong bases, strong oxidizers.

**7.3. Specific End Use(S)** For professional use only.

## **SECTION 8: Exposure Controls/Personal Protection**

#### 8.1. Control Parameters

Silica, amorphous, fumed, crystalline-free (112945-52-5)				
Austria	MAK (mg/m³)	4 mg/m³ (inhalable fraction (Silica, amorphous)		
1-Propanamine, 3-(triet	hoxysilyl)- (919-30-2)			
Finland	HTP-arvo (8h) (mg/m³)	28 mg/m³		
Finland	HTP-arvo (8h) (ppm)	3 ppm		
Finland	HTP-arvo (15 min)	55 mg/m³		
Finland	HTP-arvo (15 min) (ppm)	6 ppm		
Tin organic compounds	5			
Austria	MAK (mg/m³)	0,1 mg/m³ (except tri-n-Butyltin compounds-inhalable fraction)		
Austria	MAK Short time value (mg/m³)	0,2 mg/m³ (except Tri-n-butyltin compounds-inhalable fraction)		
Austria	OEL chemical category (AT)	Skin notation except Tri-n-butyItin compounds		
Belgium	Limit value (mg/m³)	0,1 mg/m³		
Belgium	Short time value (mg/m³)	0,2 mg/m³		
Belgium	OEL chemical category (BE)	Skin		
Bulgaria	OEL TWA (mg/m³)	0,1 mg/m³		
Croatia	GVI (granična vrijednost izloženosti) (mg/m³)	0,1 mg/m³ (except Cyhexatin)		
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m³)	0,2 mg/m³ (except Cyhexatin)		
Czech Republic	Expoziční limity (PEL) (mg/m³)	0,1 mg/m³		
Czech Republic	OEL chemical category (CZ)	Potential for cutaneous absorption		
Denmark	Grænsevædi (8 timer) (mg/m³)	0,1 mg/m³ (except Tri-n-butyltin compounds)		
Estonia	OEL TWA (mg/m³)	0,1 mg/m³		
Estonia	OEL STEL (mg/m³)	0,2 mg/m³		
Estonia	OEL chemical category (ET)	Skin notation		

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

According to Regulation (EC) No. 1907/2006 (REACH		1
Finland	HTP-arvo (8h) (mg/m³)	0,1 mg/m³
Finland	HTP-arvo (15 min)	0,3 mg/m³
Finland	OEL chemical category (FI)	Potential for cutaneous absorption
France	VLE (mg/m³)	0,2 mg/m³
France	VME (mg/m³)	0,1 mg/m³
Greece	OEL TWA (mg/m³)	0,1 mg/m³
Greece	OEL STEL (mg/m³)	0,2 mg/m³
Greece	OEL chemical category (GR)	skin - potential for cutaneous
		absorption
Hungary	AK-érték	0,1 mg/m³
Hungary	CK-érték	0,4 mg/m³
Hungary	OEL chemical category (HU)	Potential for cutaneous absorption
Ireland	OEL (8 hours ref) (mg/m³)	0,1 mg/m³
Ireland	OEL (15 min ref) (mg/m3)	0,2 mg/m³
Lithuania	IPRV (mg/m³)	0,1 mg/m³
Lithuania	TPRV (mg/m³)	0,2 mg/m³
Lithuania	OEL chemical category (LT)	Skin notation
Norway	Grenseverdier (AN) (mg/m³)	0,1 mg/m³
Norway	Grenseverdier (Korttidsverdi)	
·	(mg/m3)	0,3 mg/m³ (value calculated)
Norway	OEL chemical category (NO)	Skin notation
Portugal	OEL TWA (mg/m³)	0,1 mg/m³
Portugal	OEL STEL (mg/m³)	0,2 mg/m³
Portugal	OEL chemical category (PT)	A4 - Not Classifiable as a Human
		Carcinogen,skin - potential for
		cutaneous exposure
Romania	OEL TWA (mg/m³)	0,05 mg/m³
Romania	OEL STEL (mg/m³)	0,15 mg/m³
Slovakia	NPHV (priemerná) (mg/m³)	0,1 mg/m³
Slovakia	NPHV (Hraničná) (mg/m³)	0,2 mg/m³
Slovakia	OEL chemical category (SK)	Potential for cutaneous absorption
Spain	VLA-ED (mg/m³)	0,1 mg/m³
Spain	VLA-EC (mg/m³)	0,2 mg/m³
Spain	OEL chemical category (ES)	skin - potential for cutaneous absorption
Sweden	nivågränsvärde (NVG)	·
	(mg/m³)	0,1 mg/m³ (total dust)
Sweden	kortidsvärde (KTV) (mg/m³)	0,2 mg/m³ (total dust)
Sweden	OEL chemical category (SE)	Skin notation
Switzerland	KZGW (mg/m³)	0,2 mg/m³ (inhalable dust)
Switzerland	MAK (mg/m³)	0,1 mg/m³ (inhalable dust)
Switzerland	OEL chemical category (CH)	Skin notation
United Kingdom	WEL TWA (mg/m³)	0,1 mg/m³ (except Cyhexatin)
United Kingdom	WEL STEL (mg/m³)	0,2 mg/m³ (except Cyhexatin)
	WEL STEL (mg/m³) WEL chemical category	0,2 mg/m³ (except Cyhexatin)  Potential for cutaneous absorption

except Cyhexatin

## 8.2. Exposure Controls

Appropriate Engineering

Controls

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.

Personal Protective Equipment

5111







Materials for Protective Clothing

Chemically resistant materials and fabrics. Wear fire/flame

resistant/retardant clothing.

Hand Protection
Eye Protection

Skin and Body Protection

Respiratory Protection

Wear protective gloves. Chemical safety goggles.

Wear suitable protective clothing.

If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory

protection.

Other Information

When using, do not eat, drink or smoke.

## SECTION 9: Physical and Chemical Hazards

## 9.1. Information on Basic Physical and Chemical Properties

Physical State Liquid
Colour Black
Odour Solvent

Odour Threshold

pH

No data available

No data available **Auto-Ignition Temperature Decomposition Temperature** No data available Flammability (Solid, Gas) Not applicable Vapour Pressure No data available Relative Vapour Density At 20 °C No data available Relative Density > 1 (Water = 1) Solubility No data available Partition Coefficient n-Octanol/Water No data available Viscosity, Kinematic No data available Viscosity, Dynamic No data available **Explosive Properties** No data available Oxidising Properties No data available

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Explosive Limits No data available

9.2. Other Information

VOC content 10 - 30 %

## **SECTION 10: Stability and Reactivity**

## 10.1. Reactivity

Reacts violently with strong oxidisers. Increased risk of fire or explosion.

## 10.2. Chemical Stability

Extremely flammable liquid and vapour. May form flammable or explosive vapour-air mixture.

#### 10.3. Possibility Of Hazardous Reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions To Avoid

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

## 10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers.

## 10.6. Hazardous Decomposition Products

Not expected to decompose under ambient conditions. Thermal decomposition may produce: Carbon oxides (CO, CO<sub>2</sub>). Silicon oxides. Hydrocarbons.

## **SECTION 11: Toxicological Information**

## 11.1. Information On Toxicological Effects

Acute Toxicity

Not classified (Based on available data, the classification criteria are not met)

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
LD50 Oral Rat	> 5000 mg/kg	
LD50 Dermal Rabbit	3000 mg/kg	
2-Butanone, O,O',O''-(methylsilyli	dyne)trioxime (22984-54-9)	
LD50 Oral Rat	2463 mg/kg	
LD50 Dermal Rat	> 2000 mg/kg	
Silica, amorphous, fumed, crysta	lline-free (112945-52-5)	
LD50 Oral Rat	3160 mg/kg	
1-Propanamine, 3-(triethoxysilyl)-	(919-30-2)	
LD50 Oral Rat	1570 mg/kg	
LD50 Dermal Rabbit	4290 mg/kg	
LC50 Inhalation Rat	> 7,35 mg/l/4h	
N-[3-(TrimethoxysilyI)propyI]-1,2-e	thanediamine (1760-24-3)	
LD50 Oral Rat	2295 mg/kg	
LD50 Dermal Rabbit	> 2000 mg/kg	
LC50 Inhalation Rat	> 1,49 mg/l/4h	
Dibutyltin dilaurate (77-58-7)		
LD50 Oral	175 mg/kg	
LD50 Dermal Rat	> 2 g/kg	
Skin Corrosion/Irritation	Causes skin irritation.	
Eye Damage/Irritation	Causes serious eye irritation.	

28/08/2020 EN (English) 9/14

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Respiratory or Skin Sensitization May cause an allergic skin reaction.

Germ Cell Mutagenicity Not classified (Based on available data, the classification

criteria are not met)

Carcinogenicity Not classified (Based on available data, the classification

criteria are not met)

Reproductive Toxicity Not classified (Based on available data,

the classification criteria are not met)

Specific Target Organ Toxicity (Single Exposure) May cause drowsiness or dizziness.

Specific Target Organ Toxicity (Repeated Exposure) Not classified (Based on available data,

the classification criteria are not met)

Aspiration Hazard May be fatal if swallowed and enters airways.

## **SECTION 12: Ecological Information**

## 12.1. Toxicity

Ecology - General Harmful to aquatic life with long lasting effects.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime (22984-54-9)			
EC50 Daphnia 1	120 mg/l (Exposure time: 48h - Species: Daphnia magna)		
1-Propanamine, 3-(triethoxysilyl)-	1-Propanamine, 3-(triethoxysilyl)- (919-30-2)		
LC50 Fish 1	934 mg/l (Danio rerio)		
EC50 Daphnia 1	331 mg/l		
ErC50 (Algae)	1000 mg/l (Scenedesmus subspicatus)		
NOEC Chronic Fish	934 mg/l (Danio rerio)		
NOEC Chronic Crustacea	94 mg/l (Daphnia magna)		
N-[3-(TrimethoxysilyI)propyI]-1,2-ethanediamine (1760-24-3)			
LC50 Fish 1	597 mg/l (Species: Danio rerio)		
EC50 Daphnia 1	81 mg/l		
ErC50 (Algae)	8,8 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata)		
NOEC Chronic Fish	344 mg/l		
NOEC Chronic Crustacea	35 mg/l		
NOEC Chronic Algae	3,1 mg/l (Pseudokirchnerella subcapitata Exposure time: 96h)		
Dibutyltin dilaurate (77-58-7)			
EC50 Daphnia 1	0,463 mg/l (Daphnia magna)		

## 12.2. Persistence and Degradability

CV-1146-2	
Persistence and Degradability	May cause long-term adverse effects in the environment.

## 12.3. Bioaccumulative Potential

CV-1146-2		
Bioaccumulative potential	Not established.	
Dibutyltin dilaurate (77-58-7)		
Log Pow 4,44		

## 12.4. Mobility in Soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other Adverse Effects

Other Information Avoid release to the environment.

## **SECTION 13: Disposal Considerations**

#### 13.1. Waste Treatment Methods

Product/Packaging Disposal Dispose of contents/container in accordance with local,

Recommendations regional, national, and international regulations.

Additional Information Handle empty containers with care because residual vapours

are flammable.

Ecology - Waste Materials Avoid release to the environment. This material is hazardous to

the aquatic environment. Keep out of sewers and waterways.

## **SECTION 14: Transport Information**

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

In accordance with ADR / RID / IMDG / IATA / ADN

		:		
ADR	IMDG	IATA	ADN	RID
14.1. UN Numbe	14.1. UN Number			
1268	1268	1268	1268	1268
14.2. UN Proper S	Shipping Name			
PETROLEUM	PETROLEUM	PETROLEUM	PETROLEUM	PETROLEUM
DISTILLATES,	DISTILLATES,	DISTILLATES,	DISTILLATES,	DISTILLATES,
N.O.S. (Naphtha	N.O.S. (Naphtha	N.O.S. (Naphtha	N.O.S. (Naphtha	N.O.S. (Naphtha
Solution)	Solution)	Solution)	Solution)	Solution)
14.3. Transport H	azard Class(Es)			
3	3	3	3	3
3	3	3	3	3
14.4. Packing Gr	oup			
14.5. Environmental Hazards				
Dangerous for	Dangerous for	Dangerous for	Dangerous for	Dangerous for
the environment:	the environment:	the environment:	the environment:	the environment:
No	No	No	No	No
	Marine pollutant :			
	No			

## 14.6. Special Precautions For User

No additional information available

## 14.7. Transport in Bulk According to Annex II of MARPOL and The IBC Code

Not applicable

28/08/2020 EN (English) 11/14

## **SECTION 15: Regulatory Information**

## 15.1. Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture

#### 15.1.1. EU-Regulations

Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

## 15.1.2. National Regulations

No additional information available

## 15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out

## **SECTION 16: Other Information**

## **Indication of Changes**

Section	Section Header	Change	Date Changed
1, 2, 4, 5, 6, 7, 9, 10, 11, 12, 13, 14, 15, 16	Minor changes to whole sections	Modified	28/08/2020
3	Composition/information on ingredients	Modified	28/08/2020
8	Exposure controls	Modified	28/08/2020

Date of Preparation or Latest Revision

Data Sources

28/08/2020

Information and data obtained and used in the authoring of this safety data sheet could come from database subscriptions, official government regulatory body websites, product/ingredient manufacturer or supplier specific information, and/or resources that include substance specific data and classifications according to GHS or their subsequent adoption of GHS. According to Regulation (EC) No. 1907/2006 (REACH)

Other Information

with its amendment Regulation (EU) 2015/830

#### Full Text of H- and EUH-statements:

Acute Tox. 4	Acute toxicity (inhalation:dust,mist) Category 4
(Inhalation:dust,mist)	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2

#### Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 1	Specific target organ toxicity — Single exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Abbreviations and Acronyms

ACGIH – American Conference of Governmental Industrial Hygienists ADN – European Agreement Concerning the International Carriage of Dangerous

Goods by Inland Waterways

ADR - European Agreement Concerning the International Carriage of Dangerous

Goods by Road

ATE - Acute Toxicity Estimate BCF - Bioconcentration Factor

BEI - Biological Exposure Indices (BEI)

BOD – Biochemical Oxygen Demand CAS No. - Chemical Abstracts Service Number

CLP – Classification, Labeling and Packaging Regulation (EC) No 1272/2008

COD – Chemical Oxygen Demand EC – European Community

EC50 - Median Effective Concentration EEC – European Economic Community

EINECS - European Inventory of Existing Commercial Chemical Substances

EmS-No. (Fire) - IMDG Emergency Schedule Fire EmS-No. (Spillage) - IMDG Emergency Schedule Spillage

EU – European Union

ErC50 - EC50 in Terms of Reduction Growth Rate

GHS - Globally Harmonized System of Classification and Labeling of Chemicals

IARC - International Agency for Research on Cancer IATA - International Air Transport Association IBC Code - International Bulk Chemical Code

IMDG - International Maritime Dangerous Goods

IPRV - Ilgalaikio Poveikio Ribinis Dydis

IOELV – Indicative Occupational Exposure Limit Value LC50 - Median Lethal Concentration

LD50 - Median Lethal Dose

LOAEL - Lowest Observed Adverse Effect Level LOEC - Lowest-Observed-Effect Concentration

Log Koc - Soil Organic Carbon-water Partitioning Coefficient

Log Kow - Octanol/water Partition Coefficient Log Pow - Ratio of the equilibrium concentration (C) of a dissolved substance in a twophase system consisting of two largely immiscible solvents, in this case octanol and

MAK - Maximum Workplace Concentration/Maximum Permissible Concentration

MARPOL - International Convention for the Prevention of Pollution

NDS - Najwyzsze Dopuszczalne Stezenie NDSCh - Najwyzsze Dopuszczalne Stezenie Chwilowe

NDSP - Najwyzsze Dopuszczalne Stezenie Pula

NOAFL - No-Observed Adverse Effect Level

NOEC - No-Observed Effect Concentration

NRD - Nevirsytinas Ribinis Dydis

NTP - National Toxicology Program OEL - Occupational Exposure Limits

PBT - Persistent, Bioaccumulative and Toxic PEL - Permissible Exposure Limit

pH – Potential Hydrogen

REACH – Registration, Evaluation, Authorisation, and Restriction of Chemicals RID – Regulations Concerning the International Carriage of Dangerous Goods by Rail

SADT - Self Accelerating Decomposition Temperature SDS - Safety Data Sheet

STEL - Short Term Exposure Limit

STOT - Specific Target Organ Toxicity TA-Luft - Technische Anleitung zur Reinhaltung der Luft

TEL TRK – Technical Guidance Concentrations ThOD – Theoretical Oxygen Demand TLM - Median Tolerance Limit

TLV - Threshold Limit Value

TPRD - Trumpalaikio Poveikio Ribinis Dydis

TRGS 510 - Technische Regel für Gefahrstoffe 510 - Lagerung von Gefahrstoffen in

ortsbeweglichen Behältern

TRGS 552 – Technische Regeln für Gefahrstoffe - N-Nitrosamine

TRGS 900 - Technische Regel für Gefahrstoffe 900 - Arbeitsplatzgrenzwerte TRGS 903 - Technische Regel für Gefahrstoffe 903 - Biologische Grenzwerte

TSCA - Toxic Substances Control Act TWA - Time Weighted Average VOC – Volatile Organic Compounds

VLA-EC - Valor Límite Ambiental Exposición de Corta Duración VLA-ED - Valor Límite Ambiental Exposición Diaria VLE – Valeur Limite D'exposition

VME – Valeur Limite De Moyenne Exposition vPvB - Very Persistent and Very Bioaccumulative

WEL – Workplace Exposure Limit WGK - Wassergefährdungsklasse

Nusil EU GHS SDS

28/08/2020 EN (English) 13/14 The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLYDISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW. NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR. SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.



# Silicone Sales & Services UK - Ireland - Benelux

© 2022 - Polymer Systems Technology Limited™ Unit 2. Network 4. Cressex Business Park, Lincoln Road, High Wycombe, Bucks. HP12 3RF

tel: +44 (0) 1494 446610

web: https://www.silicone-polymers.com

email: sales@silicone-polymers.co.uk

